

## **STANDARDS**

- AS 2870 Residential slabs and footings Construction
- AS/NZS 4671 Steel reinforcing materials
- AS/NZS 4600 Cold-formed steel structures
- AS 3678 Structural steel Hot-rolled plates, floorplates and slabs
- AS 1554 (set) Structural steel welding
- AS 4680 Hot-dip galvanized (zinc) coatings on fabricated ferrous articles

## Note:

This footing has been designed based on standard sandy soil conditions. Final concrete footing dimensions and reinforecement cage length may require adjustment depending on actual site soil classification.

Recommend concrete strength: 32 MPa



			Recomm	ena concre	te strength : 32 MPa.
PROPRIETARY AND CONFIDENTIAL			NAME	DATE	PART NUMBER : PM30-8-500-900-3500
This drawing and the information contained herein are the exclusive property of Vizona Pty Ltd. Any reproduction, disclosure, or distribution-whether in part or in whole-without the prior written consent of Vizona Pty Ltd is stribly prohibiled, except where such use is for the express purpose of preparing specifications, project documentation, or design briefs in connection with the intended use of the products by architects, engineers, or related professionals.		DRAWN	MANH P.	08.07.2025	PW30-6-500-900-3500
		CHECKED	BMS	09.07.2025	TITLE:
		REVISED	GMC	09.07.2025	
SCALE: AS SHOWN					FOOT CAGE M30x8-500mm PCD SUIT 900 DIA. x 3500mm
PRODUCT FINISH: H.D.G	PRODUCT WEIGHT: 176.8 kg.				
(HOT DIPPED GALVANIZED)		COPYRIGHT			
CUSTOMER APPROVAL :		This document is the intellectual property of Vizona Pty Ltd.			
CUSTOMER NAME / PROJECT :		It must not be copied, traced, reproduced, lent, or disclosed to any third party without the prior written consent of Vizona Pty Ltd, except where such distribution is necessary for professional design or project coordination directly relating			SIZE   DWG. NO.
1				iddon diroody roldding	OUEET 4 OF 4