

STANDARDS

- AS 2870 Residential slabs and footings Construction
- AS/NZS 4671 Steel reinforcing materials
- AS/NZS 4600 Cold-formed steel structures
- AS 3678 Structural steel Hot-rolled plates, floorplates and slabs
- AS 1554 (set) Structural steel welding
- AS 4680 Hot-dip galvanized (zinc) coatings on fabricated ferrous articles

Note:

This footing has been designed based on standard sandy soil conditions. Final concrete footing dimensions and reinforecement cage length may require adjustment depending on actual site soil classification.

Recommend concrete strength: 32 MPa



Vizona Ptv Ltd info@vizona.com.au www.vizona.com.au

Recommend concrete strength : 32 MPa.				
PROPRIETARY AND CONFIDENTIAL		NAME	DATE	PART NUMBER : DM 20 9 500 000 3500
This drawing and the information contained herein are the exclusive property of Vizona Pty Ltd. Any reproduction, disclosure, or distribution—whether in part or in whole—without the prior written	DRAWN	MANH P.	08.07.2025	PM30-8-500-900-3500
consent of Vizona Pty Ltd is strictly prohibited, except where such use is for the express purpose of preparing specifications, project documentation, or design briefs in connection with the intended use of the products by architects, engineers, or related professionals.	CHECKED	BMS	09.07.2025	TITLE :
	REVISED	GMC	09.07.2025	FOOT CAGE M30x8-500mm PCD
SCALE: AS SHOWN				FOOT CAGE M30x8-500mm PCD SUIT 900 DIA. x 3500mm
PRODUCT FINISH: H.D.G PRODUCT WEIGHT: 176.8 kg.	1			
(HOT DIPPED GALVANIZED)	COPYRIGHT		HT_	
CUSTOMER APPROVAL : CUSTOMER NAME / PROJECT :	This document is the intellectual property of Vizona Pty Ltd. It must not be copied, traced, reproduced, lent, or disclosed to any third party without the prior written consent of Vizona Pty Ltd, except where such distribution is necessary for professional design or project coordination directly relating to the intended application of the products described herein.		iced, lent, or disclosed tten consent of Vizona in is necessary for	
				SHEET 1 OF 1