

- AS/NZS 4600 Cold-formed steel structures
- AS 3678 Structural steel Hot-rolled plates, floorplates and slabs
- AS 1554 (set) Structural steel welding
- AS 4680 Hot-dip galvanized (zinc) coatings on fabricated ferrous articles

## Note:

This footing has been designed based on standard sandy soil conditions. Final concrete footing dimensions and reinforecement cage length may require adjustment depending on actual site soil classification. Recommend concrete strength: 32 MPa.



Vizona Ptv Ltd info@vizona.com.au www.vizona.com.au

					<b>g</b>	
PROPRIETARY AND CONFIDENTIAL			NAME	DATE	PART NUMBER :	
This drawing and the information contained herein are the exclusive property of Vizona Pty Ltd. Any reproduction, disclosure, or distribution-whether in part or in whole-without the prior written consent of Vizona Pty Ltd is strictly prohibiled, except where such use is for the express purpose of preparing specifications, project documentation, or design briefs in connection with the intended use of the products by architects, engineers, or related professionals.		DRAWN	MANH P.	08.07.2025	PM30-8-800-1200-3900	
		CHECKED	BMS	09.07.2025	TITLE:  FOOT CAGE M30x8-800mm PCD SUIT 1200 DIA. x 3900mm	
		REVISED	GMC	09.07.2025		
SCALE: AS SHOWN						
PRODUCT FINISH: H.D.G	PRODUCT WEIGHT: 302 kg.	1			2011 1200 Bir (: X 0000111111	
(HOT DIPPED GALVANIZED)	*NOT INCLUDING THE CONCRETE PILE	COPYRIGHT		HT_		
CUSTOMER NAME / PROJECT :		This document is the intellectual property of Vizona Pty Ltd. It must not be copied, traced, reproduced, lent, or disclosed to any third party without the prior written consent of Vizona Pty Ltd, except where such distribution is necessary for professional design or project coordination directly relating				REV.
		to the intended application of the products described herein			SHEET 1 OF 1	