

- AS/NZS 4600 Cold-formed steel structures
- AS 3678 Structural steel Hot-rolled plates, floorplates and slabs
- AS 1554 (set) Structural steel welding
- AS 4680 Hot-dip galvanized (zinc) coatings on fabricated ferrous articles

## Note:

This footing has been designed based on standard sandy soil conditions. Final concrete footing dimensions and reinforecement cage length may require adjustment depending on actual site soil classification.



		Re	commend	concrete st	rength: 32 MPa.	
PROPRIETARY AND CONFIDENTIAL			NAME	DATE	PART NUMBER :	
This drawing and the information contained herein are the exclusive property of Vizona Pty Ltd. Any reproduction, disclosure, or distribution-whether in part or in whole-without the prior written consent of Vizona Pty Ltd is strictly prohibited, except where such use is for the express purpose of preparing specifications, project documentation, or design briefs in connection with the intended use of the products by architects, engineers, or related professionals.		DRAWN	MANH P.	08.07.2025	PM33-4-538-900-3100	
		CHECKED	BMS	09.07.2025	FOOT CAGE M33x4-538mm PCD SUIT 900 DIA. x 3100mm	
		REVISED	GMC	09.07.2025		
SCALE: AS SHOWN						
PRODUCT FINISH: H.D.G	PRODUCT WEIGHT: 107.4 kg.				COTT GOODIN. X GTGGIIIIII	
(HOT DIPPED GALVANIZED)		COPYRIGHT		HT	1	
CUSTOMER APPROVAL:		This document is the intellectual property of Vizona Pty Ltd.				
CUSTOMER NAME / PROJECT :		It must not be copied, traced, reproduced, lent, or disclosed to any third party without the prior written consent of Vizona Pty Ltd, except where such distribution is necessary for professional design or project coordination directly relating			SIZE DWG. NO. VDWG-3008-F	EV.
		to the intended application of the products described herein			SHEET 1 OF 1	