

STANDARDS

All products shall conform to the following Australian Standards:

- AS 2159 Piling Design and installation
- AS 2870 Residential slabs and footings Construction
- AS/NZS 4671 Steel reinforcing materials
- AS/NZS 4600 Cold-formed steel structures
- AS 3678 Structural steel Hot-rolled plates, floorplates and slabs
- AS 1554 (set) Structural steel welding
- AS 4680 Hot-dip galvanized (zinc) coatings on fabricated ferrous articles

Note:

This footing has been designed based on standard sandy soil conditions. Final concrete footing dimensions and reinforecement cage length may require adjustment depending on actual site soil classification.

Recommend concrete strength: 32 MPa.



Vizona Ptv Ltd info@vizona.com.au www.vizona.com.au

PROPRIETARY AND CONFIDENTIAL			NAME	DATE	PART NUMBER :	
This drawing and the information contained herein are the exclusive property of Vizona Pty Ltd. Any reproduction, disclosure, or distribution-whether in part or in whole-without the prior written consent of Vizona Pty Ltd is strictly prohibited, except where such use is for the express purpose of preparing specifications, project documentation, or design briefs in connection with the intended use of the products by architects, engineers, or related professionals.		DRAWN	MANH P.	08.07.2025	RBF-4M33-538	
		CHECKED	BMS	09.07.2025	TITLE : RAG BOLT & FORMER PLATE	
		REVISED	GMC	09.07.2025		
SCALE: AS SHOWN					33mm U BOLT 3mm thk SPACER	
PRODUCT FINISH: H.D.G	PRODUCT WEIGHT: 34.2 kg				Commo Boet omm tint of Albert	
(HOT DIPPED GALVANIZED)		COPYRIGHT		HT_		
CUSTOMER NAME / PROJECT :		This document is the intellectual property of Vizona Pty Ltd. It must not be copied, traced, reproduced, lent, or disclosed to any third party without the prior written consent of Vizona Pty Ltd, except where such distribution is necessary for professional design or project coordination directly relating to the intended application of the products described herein.				
						REV.
					SHEET 1 OF 1	