

- AS/NZS 4671 Steel reinforcing materials
- AS/NZS 4600 Cold-formed steel structures
- AS 3678 Structural steel Hot-rolled plates, floorplates and slabs
- AS 1554 (set) Structural steel welding
- AS 4680 Hot-dip galvanized (zinc) coatings on fabricated ferrous articles

## Note:

This footing has been designed based on standard sandy soil conditions. Final concrete footing dimensions and reinforecement cage length may require adjustment depending on actual site soil classification.

Recommend concrete strength: 32 MPa.



Vizona Pty Ltd 1300 250 150 info@vizona.com.au www.vizona.com.au

PROPRIETARY AND CONFIDENTIAL			NAME	DATE	PART NUMBER :	
This drawing and the information contained herein are the exclusive property of Vizona Pty Ltd. Any reproduction, disclosure, or distribution-whether in part or in whole-without the prior written consent of Vizona Pty Ltd is strictly prohibited, except where such use is for the express purpose of preparing specifications, project documentation, or design briefs in connection with the intended use of the products by architects, engineers, or related professionals.		DRAWN	MANH P.	08.07.2025	RBF-8M30-600	
		CHECKED	BMS	09.07.2025	TITLE :	
		REVISED	GMC	09.07.2025		
SCALE: AS SHOWN					RAG BOLT & FORMER PLATE 30mm J BOLT 5mm thk SPACER	
PRODUCT FINISH: H.D.G	PRODUCT WEIGHT: 65 kg.	1			COMMINITOR BOLL COMMINICAL ACTIVITIES	
(HOT DIPPED GALVANIZED)			COPYRIGHT		]	
CUSTOMER APPROVAL:		This document is the intellectual property of Vizona Pty Ltd.				
CUSTOMER NAME / PROJECT :		It must not be copied, traced, reproduced, lent, or disclosed to any third party without the prior written consent of Vizona Pty Ltd, except where such distribution is necessary for professional design or project coordination directly relating			A4 VDWG-4007-R	REV.
		professional accign of project coordination allocally rolating			OUEET 4 OF 4	